



758 South Broad Street · Toccoa, Georgia 30577
Telephone: 404.915.8352 · Fax: 800.470.3537
Email: sales@thecourtstore.com

CRACKLASTIC

PRE-COLORED ELASTOMERIC PATCHING COMPOUND

DESCRIPTION

CRACKLASTIC is a high strength, pre-colored, elastomeric patching compound specifically designed for filling cracks on painted tennis courts and other sport surfaces when court re-coating is not planned. CrackLastic is compatible with asphalt and concrete on cracks up to 1/2" wide.

COLORS

Dark Green · Light Green · Red · Dark Red · Burgundy · Dark Blue · Light Blue · Tan · Gray · Brown · Neutral

APPLICATOR

Use a flexible steel straightedge up to 6" wide, such as a drywall taping knife or a putty knife.

DRYING TIME

Patches (up to 1/2" wide) will dry in about 24 hours under optimal outdoor temperature and humidity conditions. Always allow CrackLastic to thoroughly dry to its full depth before application of another layer or color-coating.

MIXING INSTRUCTIONS

This product is ready-to-use. No mixing other is required.

COVERAGE

One gallon pail will patch approximately 150 lineal feet of cracks 1/4" wide by 1/2" deep.

CRACK PREPARATION AND APPLICATION

Cracks to be repaired must be sound, and free of dirt, dust grease, mildew, vegetation and other foreign matter. Fill cracks completely with CrackLastic. Smooth flush to adjoining pavement with a putty knife or drywall taping knife. Feather edges creating a smooth transition to the adjoining playing surface. Allow material to dry overnight before permitting play, or applying EnviroCoat acrylic sport coatings

LIMITATIONS

Do not apply when surface temperature is below 50° F (10° C), or expected to fall below this temperature or when rain is imminent within 24 hours. Do not apply if surface temperature is above 130° F (55° C). Always allow application to dry thoroughly before subsequent applications. Keep containers tightly closed when not in use. Keep from freezing. Do not store in direct sunlight.

CLEAN-UP

Remove all spilled material immediately. Clean all equipment with water immediately after use.

CAUTION

Do not take internally. Keep out of reach of children.

ENVIRONMENTAL SPORT COATINGS LIMITED WARRANTY

Environmental Sport Coatings warrants, to the original customer purchaser only, that the product, which is the subject of this sale is free from defects in material or workmanship. This warranty will remain effective for the shorter period of one (1) year from the date of purchase or until the sale or transfer of the product. In the event that this product does not conform to this written warranty, Environmental Sport Coatings will replace this product or refund the full purchase price. This warranty does not cover damage caused by this product when used for purposes other than that for which it was produced, or any other abuse or misuse by the purchaser. Environmental Sport Coatings shall not be liable for any incidental or consequential damages resulting from the use of this product, including, but not limited to, property damage, loss of profits, loss of savings or revenue or the cost of any substitute equipment, facilities, or services. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. **ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE LIMITED TO ONE (1) YEAR.** Some states do not allow limitations on how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.