



2091 Burnette Rd · Toccoa, Georgia 30577
Telephone: 404.915.8352 · Fax: 800.470.3537
Email: sales@thecourtstore.com

ENVIROCOAT

ACRYLIC READY-TO-USE COLOR

DESCRIPTION

ENVIROCOAT, Acrylic Ready-To-Use Color Concentrate is a highly pigmented, sand filled, 100% acrylic emulsion designed for on-site mixing with water to produce a long-lasting finish for tennis courts. ENVIROCOAT provides a uniform texture that can be adjusted by varying the size and amount of sand added to the mix. This coating, used in conjunction with recommended Environmental Sport Coatings products, will provide a long lasting, fade resistant finish with superior play characteristics.

USE

Asphalt and concrete tennis courts and other recreational surfaces.

COLORS

Winter Green · Spring Green · Dark Blue · Light Blue · Red · Burgundy · Adobe Tan · Brown · Gray

SURFACE PREPARATION AND APPLICATION

New asphalt must cure for 14 days under normal summer drying conditions, longer during cooler weather and be clean and free of all grease, oil, dirt and any other foreign matter. Clean by washing with a high-pressure water hose or blow clean with an air broom. Remove any grease or oil with a strong detergent and then flush thoroughly with water. Were oil or grease penetrated, it may be necessary to remove affected asphalt and patch with TRUPATCH. Areas holding more than 1/8" of water one hour after flooding shall be patched and all cracks filled with TRUPATCH, before applying this product. Apply ENVIROFILL with a rubber squeegee. Pour windrow parallel to one of the directions of the surface. Spread evenly by walking in one direction and then reversing the direction. Do not "overwork" and always maintain a wet edge. Inspect the surface and scrape off any ridges, lumps or other foreign matter before proceeding with additional coats.

CONCRETE COURTS

See ENVIROBOND specifications.

APPLICATOR

Use a standard squeegee with a 50 to 70 durometer, flexible rubber blade up to 48" in width.

DRYING TIME

One hour under optimum outdoor temperature and humidity conditions. Always allow coat to thoroughly dry to it's full depth before application of subsequent coats.

IMPORTANT

Allow a minimum of 24 hours drying before playing on newly surfaced areas. Do not play on surface when wet for a period of thirty days after the application of coatings.

MIX

Sand gradation in the product is 80-100 mesh. Quantities of water will vary slightly depending upon gradations of sand used.

- ENVIROCOAT –3.5 gallons
- Water – 1.5 gallons
- Yield – 5 gallons
- Mix thoroughly with suitable mixer. Use clean potable water only.

COVERAGE

A typical tennis court measuring 60' X 120' with a relatively smooth surface will require approximately 75 gallons of ENVIROCOAT Ready-To-Use mix per coat on a smooth surface. Coverage is approximately 100 square feet per gallon. The amount of material used will vary due to the texture of the existing surface.

NUMBER OF COATS

New surfaces – Minimum of two coats after the surface has been properly filled using ENVIROFILL.
Resurfacing – Two to three coats of EnviroCoat, depending on condition of surface

LIMITATIONS

Do not apply when surface temperature is below 40° F or when rain or high humidity is imminent. Do not apply if surface temperature is above 130° F. Always allow coat to dry thoroughly before application of subsequent coats. Keep containers tightly closed when not in use. Keep from freezing. Do not store in direct sunlight.

CLEAN-UP

Remove all spilled material immediately. Clean all equipment with water immediately after use.

CAUTION

Do not take internally. Keep out of reach of children.

ENVIRONMENTAL SPORT COATINGS LIMITED WARRANTY

Environmental Sport Coatings, Inc. warrants, to the original customer purchaser only, that the product, which is the subject of this sale is free from defects in material or workmanship. This warranty will remain effective for the shorter period of one (1) year from the date of purchase or until the sale or transfer of the product. In the event that this product does not conform to this written warranty, Environmental Sport Coatings, Inc. will replace this product or refund the full purchase price. This warranty does not cover damage caused by this product when used for purposes other than that for which it was produced, or any other abuse or misuse by the purchaser. Environmental Sport Coatings, Inc. shall not be liable for any incidental or consequential damages resulting from the use of this product, including, but not limited to, property damage, loss of profits, loss of savings or revenue or the cost of any substitute equipment, facilities, or services. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE LIMITED TO ONE (1) YEAR. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.