



758 South Broad St. - Toccoa, Georgia 30577  
Telephone: 404.915.8352 - Fax: 800.470.3537  
Email: sales@thecourtstore.com

## **ENVIROFILL ACRYLIC RESURFACER READY-TO-USE**

### **DESCRIPTION**

ENVIROFILL Acrylic Resurfacer is a, sand filled, 100% acrylic emulsion designed specifically for on-site mixing with water to produce a heavy bodied filler coat that reduces surface porosity of asphalt pavement and provides a uniformly textured substrate on which to apply Environmental Sport Coatings Color Coating System.

### **USE**

Apply over asphalt that is to be color-coated with Environmental Sport Coatings Color Coating System.

### **APPLICATOR**

Use a standard squeegee with a 50 to 70 durometer, flexible rubber blade up to 48" in width.

### **DRYING TIME**

One hour under optimum outdoor temperature and humidity conditions. Always allow coat to thoroughly dry to it's full depth before application of subsequent coats.

### **MIX**

Sand gradation is between 60 and 80 Mesh. Quantities of water can vary slightly depending upon the thickness and filling properties desired.

<b><u>5 GALLON PAIL</u></b>		<b><u>30 GALLON DRUM</u></b>		<b><u>55 GALLON DRUM</u></b>	
EnviroFill (in pail)	3.5 gallons	EnviroFill (in drum)	23 gallons	EnviroFill (in drum)	55 gallons
Water	1.5 gallons	Water	7 gallons	Water	27.5 gallons
Yield	5 gallons	Yield	30 gallons	Yield	82.5 gallons
Mix thoroughly with suitable mixer.		Mix thoroughly with suitable mixer.		Mix thoroughly with suitable mixer.	
Use clean potable water only.		Use clean potable water only.		Use clean potable water only.	

### **COVERAGE**

A typical new asphalt tennis court measuring 60' X 120' will require 150 gallons of ENVIROFILL. Coverage is between 40 –100 square feet per gallon of mix. The amount of material used will vary due to the porosity of the surface.

### **SURFACE PREPARATION AND APPLICATION**

The asphalt to be surfaced must be sound, and free of dirt, dust grease, mildew and other foreign matter. New asphalt shall be allowed to cure a minimum of 14 days prior to the application of this product. Curing time may be longer if cold or wet conditions prevail. Areas holding more than 1/8" of water one hour after flooding shall be patched and all cracks filled with TRUPATCH before applying this product. Apply ENVIROFILL with a rubber squeegee. Pour windrow parallel to one of the directions of the surface. Spread evenly by walking in one direction and then reversing the direction. Do not "overwork" and always maintain a wet edge. If multiple coats are applied, inspect coating and scrape off any ridges, lumps or other foreign matter and then apply a uniform coat 90° to previous coat. Follow with Environmental Sport Coatings Color-Coating System.

### **LIMITATIONS**

Do not apply when surface temperature is below 40° F (10° C) or when rain or high humidity is imminent. Do not apply if surface temperature is above 130° F (55° C). Always allow coat to dry thoroughly before application of subsequent coats. Keep containers tightly closed when not in use. Keep from freezing. Do not store in direct sunlight.

**CLEAN-UP**

Remove all spilled material immediately. Clean all equipment with water immediately after use. **CAUTION** Do not take internally. Keep out of reach of children.

**ENVIRONMENTAL SPORT COATINGS LIMITED WARRANTY**

Environmental Sport Coatings, Inc. warrants, to the original customer purchaser only, that the product, which is the subject of this sale is free from defects in material or workmanship. This warranty will remain effective for the shorter period of one (1) year from the date of purchase or until the sale or transfer of the product. In the event that this product does not conform to this written warranty, Environmental Sport Coatings, Inc. will replace this product or refund the full purchase price. This warranty does not cover damage caused by this product when used for purposes other than that for which it was produced, or any other abuse or misuse by the purchaser. Environmental Sport Coatings, Inc. shall not be liable for any incidental or consequential damages resulting from the use of this product, including, but not limited to, property damage, loss of profits, loss of savings or revenue or the cost of any substitute equipment, facilities, or services. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. **ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE LIMITED TO ONE (1) YEAR.** Some states do not allow limitations on how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.