



758 South Broad Street · Toccoa, Georgia 30577
Telephone: 404.915.8352 · Fax: 800.470.3537
Email: sales@thecourtstore.com

ENVIROLINE

ACRYLIC WHITE LINE PAINT

DESCRIPTION

ENVIROLINE is carefully formulated with 100% acrylic emulsion for use on tennis courts, running tracks, basketball courts and other recreational areas. The use of ENVIROLINE results in clean, clear-cut permanent lines. ENVIROLINE is designed to give superior lines on all types of asphalt and acrylic surfaces and are recommended for use over all Environmental Sport Coatings systems. ENVIROLINE is available in white and all ten of our standard EnviroCoat colors.

USE

Tennis courts, running tracks, basketball courts, asphalt, and other recreational areas.

COLORS

White · Yellow · Dark Green · Light Green · Dark Blue · Light Blue · Red · Dark Red · Burgundy · Tan · Brown · Gray

SURFACE PREPARATION AND APPLICATION

New asphalt must cure for 14 days under normal summer drying conditions, longer during cooler weather and be clean and free of all grease, oil, dirt and any other foreign matter. Clean by washing with a high-pressure water hose or blow clean with an air broom. Remove any grease or oil with a strong detergent and then flush thoroughly with water.

DRYING TIME

One hour under optimum outdoor temperature and humidity conditions. Always allow coat to thoroughly dry to it's full depth before application of subsequent coats.

IMPORTANT

Allow a minimum of 24 hours drying before playing on newly surfaced areas. Do not play on surface when wet for a period of thirty days after the application of coatings.

DILUTION

Apply as is with brush or roller. For spray application add up to 20% water.

COVERAGE

Coverage is approximately 480 lineal feet of 2" lines per coat, per gallon. One gallon per tennis court is usually sufficient for one coat.

NUMBER OF COATS

Two coats recommended.

LIMITATIONS

Do not apply when surface temperature is below 50° F (10° C) or when rain or high humidity is imminent. Do not apply if surface temperature is above 130° F (55° C). Always allow coat to dry thoroughly before application of subsequent coats. Keep containers tightly closed when not in use. Keep from freezing. Do not store in direct sunlight.

CLEAN-UP

Remove all spilled material immediately. Clean all equipment with water immediately after use.

CAUTION

Do not take internally. Keep out of reach of children.

ENVIRONMENTAL SPORT COATINGS LIMITED WARRANTY

Environmental Sport Coatings, Inc. warrants, to the original customer purchaser only, that the product, which is the subject of this sale is free from defects in material or workmanship. This warranty will remain effective for the shorter period of one (1) year from the date of purchase or until the sale or transfer of the product. In the event that this product does not conform to this written warranty, Environmental Sport Coatings, Inc. will replace this product or refund the full purchase price. This warranty does not cover damage caused by this product when used for purposes other than that for which it was produced, or any other abuse or misuse by the purchaser.

Environmental Sport Coatings, Inc. shall not be liable for any incidental or consequential damages resulting from the use of this product, including, but not limited to, property damage, loss of profits, loss of savings or revenue or the cost of any substitute equipment, facilities, or services. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A SPECIFIC PURPOSE ARE LIMITED TO ONE (1) YEAR. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.